

Corner-reflector Antenna Vertical Polarization Half-power Beam Width

360–490

V

44°


KATHREIN
Antennen · Electronic

VPol Corner 360–490 44° 11dBi


Type No.	K 73 12 21
Frequency range	360 – 490 MHz
Polarization	Vertical
Gain	11 dBi
Half-power beam width	H-plane: 44° E-plane: 67°
Impedance	50 Ω
VSWR	< 1.5 at 360 – 490 MHz < 1.3 at 400 – 470 MHz
Max. power	180 W (at 50 °C ambient temperature)



- Scope of supply:** Antenna with weather protective casing for straight connectors, mounting kit included.
- Material:** Radiator and reflector: Weather-resistant aluminum.
Mounting U-bolt: Stainless steel.
All screws and nuts: Stainless steel.
- Attachment:** To tubular masts of 30 – 54 mm diameter using supplied U-bolts.
- Special features:** The reflector screen folds together for transport.
- Grounding:** All metal parts of the antenna including the mounting kit and the inner conductor are DC grounded.



Horizontal Pattern



Vertical Pattern

Mechanical specifications

Input	N female
Weight	2.8 kg
Wind load	140 N (at 150 km/h)
Max. wind velocity	150 km/h
Packing size	842 x 524 x 187 mm
Height/width/depth	500 / 1155 / 577 mm

936.034/a Subject to alteration.

All specifications are subject to change without notice.
The latest specifications are available at www.kathreinusa.com

K 73 12 21 Page 1 of 2

Environmental conditions: Kathrein antennas are designed to operate under the environmental conditions as described in ETS 300 019-1-4 class 4.1 E.

The antennas exceed this standard with regard to the following items:

- Low temperature: –55 °C
- High temperature (dry): +60 °C

Environmental tests: Kathrein antennas have passed environmental tests as recommended in ETS 300 019-2-4. The homogenous design of Kathrein's antenna families use identical modules and materials. Extensive tests have been performed on typical samples and modules.

Please note: **As a result of more stringent legal regulations and judgements regarding product liability, we are obliged to point out certain risks that may arise when products are used under extraordinary operating conditions.**

The mechanical design is based on the environmental conditions as stipulated in ETS 300 019-1-4, which includes the static mechanical load imposed on an antenna by wind at maximum velocity. Extraordinary operating conditions, such as heavy icing or exceptional dynamic stress (e.g. strain caused by oscillating support structures), may result in the breakage of an antenna or even cause it to fall to the ground. These facts must be considered during the site planning process.

The installation team must be properly qualified and also be familiar with the relevant national safety regulations.

The details given in our data sheets have to be followed carefully when installing the antennas and accessories.

The limits for the coupling torque of RF-connectors, recommended by the connector manufacturers must be obeyed.

Any previous datasheet issues have now become invalid.

